

# Eaton Switched ePDUs



Network and serial connections located at the top of the unit.

Designed for data centers needing remote site management, the switched ePDUs provide remote power monitoring of both the voltage and current.

These units employ multiple configurations, available in 0U and 2U rack mount, and 42" or 66" vertical lengths, providing individual on/off/reboot control of up to 24 receptacles.

## Features

### Environmental

This provides for external temperature, humidity and contact closure environmental sensing.

### Strapping

Daisy chain up to 24 switched ePDU for control from one IP address.

### Power Monitoring/Current Metering

Both the current and voltage can be monitored, allowing the user to properly load balance the unit.

### Local Current Meter Display

A local two-digit LED display outputs the total current per section and can be read from up to 20 feet away.

### Outlet Control

Remotely manage power at the outlet level to turn power on/off or reboot devices.



Powering Business Worldwide



**PW103SW0U152**



**PW105SW2U223**



**PW105SW0U154**



**PW306SW0U156**



**PW309SW0U178**

**Vertical mounting**



SUB-HRDWARE-017 - Slotted mounting bracket and tool-less mounting buttons included in box.

**Environmental**

- Operating Temperature is 0 to 50 C
- Storage Temperature is -40 to 70 C
- Altitude Maximum 10,000 ft.
- Relative Humidity is 95% Max Non-Condensing

| Catalog Number      | Style Number     | Input Plug      | Function | Cord length | Orientation | Receptacles        | Dimensions (H x W x D, in.) |
|---------------------|------------------|-----------------|----------|-------------|-------------|--------------------|-----------------------------|
| <b>PW101SW0U224</b> | IPV70A1-EP1-09S  | 5-15P           | SW       | 9'          | 0U          | (16) 5-15R         | 66 x 2 x 1.89               |
| <b>PW102SW0U150</b> | IPV42A2-EP1-009L | L5-20P          | SW       | 9'          | 0U          | (8) 5-15R          | 42 x 2 x 1.89               |
| <b>PW102SW0U151</b> | IPV70A5-EP1-09L  | L5-20P          | SW       | 9'          | 0U          | (24) 5-15R         | 66 x 2 x 1.89               |
| <b>PW103SW0U152</b> | IPV70C5-EP1-09L  | L5-30P          | SW       | 9'          | 0U          | (16) 5-15R         | 66 x 2 x 1.89               |
| <b>PW103SW0U153</b> | IPV70B2-EP1-10L  | L6-20P          | SW       | 9'          | 0U          | (24) C13           | 66 x 2 x 1.89               |
| <b>PW105SW2U223</b> | IPC36F4N2USW09L  | L6-30P          | SW       | 9'          | 2U          | (20) C13, (4) C20  | 3.5 x 19 x 9.5              |
| <b>PW105SW0U154</b> | IPV70F3-EP1-09L  | L6-30P          | SW       | 9'          | 0U          | (16) C13           | 66 x 2 x 1.89               |
| <b>PW306SW0U155</b> | IPV70K1-EP1-09L  | L21-20P         | SW       | 9'          | 0U          | (24) 5-15R         | 66 x 2 x 1.89               |
| <b>PW306SW0U156</b> | IPV70M1-EP1-09L  | L21-20P         | SW       | 9'          | 0U          | (24) C13           | 66 x 2 x 1.89               |
| <b>PW309SW0U178</b> | IPV70R1-EP1-09L  | L21-30P         | SW       | 9'          | 0U          | (24) C13           | 66 x 2 x 3.5                |
| <b>PW317SW0U401</b> | IPV70T1-EP1-12L  | IEC60309 4609PW | SW       | 12'         | 0U          | (12) C13, (12) C19 | 66 x 2 x 4                  |
| <b>PW317SW0U400</b> | IPV70T2-EP1-12L  | IEC60309 4609PW | SW       | 12'         | 0U          | (18) C13, (6) C19  | 66 x 2 x 4                  |

**Environmental Probes** (ordered separately)

| Catalog Number        | Description                  |
|-----------------------|------------------------------|
| <b>SENSOR-T1H1-10</b> | 10', (1) Temp., (1) Humidity |
| <b>SENSOR-T2H1-10</b> | 10', (2) Temp., (1) Humidity |
| <b>SENSOR-T1-10</b>   | 10', (1) Temp.               |
| <b>SENSOR-T2-10</b>   | 10', (2) Temp.               |



Temperature Sensors

**Functions Key:**

SW - Switched

UNITED STATES  
8609 Six Forks Road  
Raleigh, NC 27615 U.S.A.  
Toll Free: 1.800.356.5794

www.epdu.com

CANADA  
Ontario: 416.798.0112  
Toll free: 1.800.461.9166

LATIN AMERICA  
South Cone: 54.11.4124.4000  
Brazil: 55.11.3616.8500  
Andean & Caribbean:  
1.949.452.9610  
Mexico & Central America:  
52.55.9000.5252

EUROPE/MIDDLE EAST/AFRICA  
Denmark: 45.3686.7910  
Finland: 358.94.52.661  
France: 33.1.6012.7400  
Germany: 49.0.7841.604.0  
Italy: 39.02.66.04.05.40  
Norway: 47.23.03.65.50  
Portugal: 55.11.3616.8500  
Sweden: 46.8.598.940.00  
United Kingdom: 44.1753.608.700

ASIA PACIFIC  
Australia: 61.2.9693.9366  
New Zealand: 64.0.3.343.3314  
China: 86.21.6361.5599  
HK/Korea/Taiwan: 852.2745.6682  
India: 91.11.4223.2300  
Singapore/SEA: 65.6825.1668

Eaton is a registered trademarks of Eaton Corporation. All other trademarks are property of their respective owners.